

the tube and to increase the burst strength of the tube. One known method of making such a tube is to physically insert a corrugated fin into a generally flattened tube after the tube has been manufactured. This is an extremely
5 difficult process since the corrugated fin to be inserted into the tube is extremely thin and subject to deformation during the insertion process.

It is also known to produce a corrugated fin or
turbulator by a stamping process. An example of such a
10 turbulator is disclosed in U.S. Patent No. 5,560,425. In this patent, the turbulator is made by stamping in a direction parallel to the fluid flow or strip direction of the turbulator and has corrugations in a direction perpendicular to the direction of the flow of the fluid or
15 strip direction.

It is further known that a turbulator for a
charged air cooler (CAC) may be formed by stamping as
described above or by roll-forming corrugation, then with a
secondary stamping for louvers. Although these methods
20 have worked well, they suffer from the disadvantage that the stamping process does not have a high production through put. Another disadvantage is that the stamping process is relatively expensive. Therefore, there is a need in the art to provide a method of using only roll

forming to manufacture tubulators in a relatively less costly manner.

SUMMARY OF THE INVENTION

5 Accordingly, the present invention is a
turbulator with offset louvers for a heat exchanger
including a plurality of corrugated fins each having a base
extending laterally and longitudinally in a strip. The
turbulator also includes a plurality of offset louvers
10 spaced along the base and extending longitudinally and
generally perpendicular to the base in an alternating
manner. The offset louvers are rolled in a direction
parallel to a longitudinal axis of the strip.

 In addition, the present invention is a method of
15 making a turbulator with offset louvers for a heat
exchanger. The method includes the steps of providing a
generally planar strip having a base extending laterally
and longitudinally. The method also includes the step of
forming a plurality of offset louvers spaced along the base
20 and extending generally perpendicular to the base in an
alternating manner such that the offset louvers extend in a
direction parallel to a longitudinal axis of the strip.

 One advantage of the present invention is that a
turbulator with offset louvers is provided for a heat
25 exchanger such as a charge air cooler for a motor vehicle.

Another advantage of the present invention is that a method of making a turbulator with offset louvers is provided. Yet another advantage of the present invention is that the method of making the turbulator with off-set louvers uses only roll forming to manufacture the turbulators, which is less costly and increases production through put. Still another advantage of the present invention is that the method of making the turbulator with offset louvers uses roll forming to make turbulator corrugations and cut louvers simultaneously. A further advantage of the present invention is that the method of making the turbulator with offset louvers has the direction of roll forming the same as the strip or fluid direction.

Other features and advantages of the present invention will be readily appreciated, as the same becomes better understood, after reading the subsequent description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a turbulator with offset louvers, according to the present invention, illustrated in operational relationship with a heat exchanger of a motor vehicle.

FIG. 2 is a sectional view taken along line 2-2 of FIG. 1.

FIG. 3 is an enlarged partial perspective view of a portion of the turbulator of FIG. 1.

FIG. 4 is a side elevational view of an apparatus for making the turbulator of FIG. 1.

5 FIG. 5 is a front elevational view of the apparatus for making the turbulator of FIG. 1.

FIG. 6 is a sectional view taken along line 6-6 of FIG. 5.

10 FIG. 7 is an enlarged view of a portion in circle 7 of FIG. 5.

FIG. 8 is a perspective view of the turbulator made with the apparatus of FIGS. 4 through 7 before being folded into its final configuration of FIG. 3.

15 **DESCRIPTION OF THE PREFERRED EMBODIMENT(S)**

Referring to the drawings and in particular FIG. 1, one embodiment of a heat exchanger 10 for a motor vehicle (not shown), such as a charge air cooler, oil cooler, evaporator, or condenser, is shown. The heat
20. exchanger 10 includes a plurality of generally parallel tubes 12 extending between oppositely disposed headers 14,16. The heat exchanger 10 includes a fluid inlet (not shown) for conducting cooling fluid into the heat exchanger 10 formed in the header 14 and an outlet (not shown) for
25 directing fluid out of the heat exchanger 10 formed in the

header 16. The heat exchanger 10 also includes a plurality of convoluted or serpentine fins 18 attached to an exterior of each of the tubes 12. The fins 18 are disposed between each of the tubes 12. The fins 18 serve as a means for
5 conducting heat away from the tubes 12 while providing additional surface area for convective heat transfer by air flowing over the heat exchanger 10. It should be appreciated that the heat exchanger 10 could be used in other applications besides motor vehicles.

10 Referring to FIGS. 1 and 2, the tube 12 extends longitudinally and is substantially flat. The tube 12 includes a base 20 being generally planar and extending laterally. The tube 12 also includes a top 22 spaced from the base 20 a predetermined distance and opposing each
15 other. The top 22 is generally planar and extends laterally. The tube 12 includes a first side 24 interposed between the base 20 and the top 22 along one side thereof. The first side 24 is generally arcuate in shape. The tube 12 also includes a second side 26 interposed between the
20 base 20 and the top 22 along the other side and opposing the first side 24 to form a channel 28. The second side 26 is generally arcuate in shape. The tube 12 is made of a metal material such as aluminum or an alloy thereof and has a cladding on its inner and outer surfaces for brazing. It

should be appreciated that the tube 12 is conventional and known in the art.

Referring to FIGS. 1 through 3 and 8, the heat exchanger 10 includes a turbulator, generally indicated at 30 and according to the present invention, disposed within the channel 28 of each of the tubes 12. In the embodiment illustrated, the turbulator 30 extends laterally and longitudinally in the form of a strip 31 that is folded or corrugated providing a series of fins 32, between folds or connecting members 33. Each fin 32 of the turbulator 30 has a generally planar base 34 extending laterally a predetermined distance and longitudinally a predetermined distance between the connecting members 33. The base 34 has a predetermined thickness such as between approximately 0.05 millimeters (mm) to approximately 0.25 mm. Each fin 32 of the turbulator 30 also has a plurality of louvers 36 spaced laterally along the base 32 and extending longitudinally to turbulate fluid flow through the channel 28. The louvers 36 have generally inverted "U" cross-sectional shape. The louvers 36 are offset generally vertically from a plane of the base 32 and extend generally perpendicular to a plane of the base 34 a predetermined distance between approximately 0.3 mm to approximately 1.0 mm. The louvers 36 extend longitudinally a predetermined distance such as between approximately 4.0 mm to

approximately 11.0 mm in a strip or fluid flow direction. The louvers 36 are spaced laterally a predetermined distance between approximately 0.80 mm to approximately 3.0 mm. The louvers 36 also extend perpendicular to the plane
5 of the base 34 in an alternating pattern such that one of the louvers 36 extends upwardly and a laterally adjacent louver 36 extends downwardly. The louvers 36 are spaced laterally in a row, which is offset from an adjacent longitudinal row of laterally spaced louvers 36 such that
10 in a longitudinal direction one of the louvers 36 extends upwardly and the longitudinally adjacent louver 36 extends downwardly. The louvers 36 are formed by roll forming the strip 31 in a direction along its longitudinal length to be described. The turbulator 30 is made of a metal material
15 such as aluminum or an alloy thereof and has a cladding on its surfaces for brazing the turbulator 30 to the tube 12. It should be appreciated that the louvers 36 are brazed to the top 22 and base 20 of the tube 12. It should also be appreciated that the louvers 36 extend longitudinally
20 generally parallel to the base 34.

Referring to FIGS. 4 through 6, an apparatus, generally indicated at 40, is shown for making the turbulator 30. The apparatus 40 includes a pair of support members 42 spaced longitudinally and extending vertically.
25 The support members 42 are secured by suitable means such

as fasteners 44 to a support surface 46. The apparatus 40 also includes a first or lower stripper plate 48 disposed adjacent the support members 42 and a second or upper stripper plate 50 disposed adjacent the lower stripper plate 48. The lower and upper stripper plates 48 and 50 are secured to the support members 42 by suitable means such as fasteners 52. The stripper plates 48 and 50 include a recess 54 being generally arcuate in shape with a plurality of channels 56 spaced laterally and extending longitudinally. In the embodiment illustrated, there are nine channels 56 spaced laterally a predetermined distance such as 0.0775 inches. The channels 56 have a predetermined width such as 0.025 inches for teeth 62 of rollers 58, 60 to be described.

As illustrated in FIGS. 4 through 7, the apparatus 40 includes a pair of rotatable rollers such as an upper roller 58 and a lower roller 60 operatively connected to supporting structure (not shown). The upper roller 58 and lower roller 60 are generally circular in shape and have a plurality of teeth 62 extending radially and circumferentially and are spaced circumferentially. The upper roller 58 is disposed in the recess 54 of the upper stripper plate 50 such that a portion of the teeth 62 are disposed in the channels 56 of the upper stripper plate 50. The lower roller 60 is disposed in the recess 54 of the

lower stripper plate 58 such that a portion of the teeth 62 are disposed in the channels 56 of the lower stripper plate 48. The base 34 of the turbulator 30 is fed into a slot or channel 64 between the upper stripper plate 50 and the lower stripper plate 48 in a longitudinal direction, which is the rolling direction for the upper and lower rollers 58 and 60. It should be appreciated that the strip 31 is roll-formed to make corrugations similar to that disclosed in U.S. Patent No. 3,214,954, the disclosure of which is hereby incorporated by reference.

As illustrated in FIGS. 6 and 7, the teeth 62 of the upper and lower rollers 58 and 60 have a base-forming portion 65 and a protruding or louver-forming portion 66. The louver-forming portion 66 extends axially and radially to form the louvers 36 of the turbulator 30 in one direction. The teeth 62 also have a tooth arc 68 and a root tip 70 to form the connecting members 33 between the fins 32. The base-forming portion 65 is disposed laterally between the louver-forming portions 66 to maintain the flat shape of the base 34 of the turbulator 30. It should be appreciated that the teeth 62 of rollers 58 and 60 engage each other to form the louvers 36 of the turbulator 30 and the flat portion or base 34 between the louvers 36 provide strength and allow a finger (not shown) to strip the turbulator 30 to form a coil or roll. It should also be

1894
 1895
 1896
 1897
 1898
 1899
 1900
 1901
 1902
 1903
 1904
 1905
 1906
 1907
 1908
 1909
 1910
 1911
 1912
 1913
 1914
 1915
 1916
 1917
 1918
 1919
 1920
 1921
 1922
 1923
 1924
 1925
 1926
 1927
 1928
 1929
 1930
 1931
 1932
 1933
 1934
 1935
 1936
 1937
 1938
 1939
 1940
 1941
 1942
 1943
 1944
 1945
 1946
 1947
 1948
 1949
 1950
 1951
 1952
 1953
 1954
 1955
 1956
 1957
 1958
 1959
 1960
 1961
 1962
 1963
 1964
 1965
 1966
 1967
 1968
 1969
 1970
 1971
 1972
 1973
 1974
 1975
 1976
 1977
 1978
 1979
 1980
 1981
 1982
 1983
 1984
 1985
 1986
 1987
 1988
 1989
 1990
 1991
 1992
 1993
 1994
 1995
 1996
 1997
 1998
 1999
 2000
 2001
 2002
 2003
 2004
 2005
 2006
 2007
 2008
 2009
 2010
 2011
 2012
 2013
 2014
 2015
 2016
 2017
 2018
 2019
 2020
 2021
 2022
 2023
 2024
 2025
 2026
 2027
 2028
 2029
 2030
 2031
 2032
 2033
 2034
 2035
 2036
 2037
 2038
 2039
 2040
 2041
 2042
 2043
 2044
 2045
 2046
 2047
 2048
 2049
 2050
 2051
 2052
 2053
 2054
 2055
 2056
 2057
 2058
 2059
 2060
 2061
 2062
 2063
 2064
 2065
 2066
 2067
 2068
 2069
 2070
 2071
 2072
 2073
 2074
 2075
 2076
 2077
 2078
 2079
 2080
 2081
 2082
 2083
 2084
 2085
 2086
 2087
 2088
 2089
 2090
 2091
 2092
 2093
 2094
 2095
 2096
 2097
 2098
 2099
 2100
 2101
 2102
 2103
 2104
 2105
 2106
 2107
 2108
 2109
 2110
 2111
 2112
 2113
 2114
 2115
 2116
 2117
 2118
 2119
 2120
 2121
 2122
 2123
 2124
 2125
 2126
 2127
 2128
 2129
 2130
 2131
 2132
 2133
 2134
 2135
 2136
 2137
 2138
 2139
 2140
 2141
 2142
 2143
 2144
 2145
 2146
 2147
 2148
 2149
 2150
 2151
 2152
 2153
 2154
 2155
 2156
 2157
 2158
 2159
 2160
 2161
 2162
 2163
 2164
 2165
 2166
 2167
 2168
 2169
 2170
 2171
 2172
 2173
 2174
 2175
 2176
 2177
 2178
 2179
 2180
 2181
 2182
 2183
 2184
 2185
 2186
 2187
 2188
 2189
 2190
 2191
 2192
 2193
 2194
 2195
 2196
 2197
 2198
 2199
 2200
 2201
 2202
 2203
 2204
 2205
 2206
 2207
 2208
 2209
 2210
 2211
 2212
 2213
 2214
 2215
 2216
 2217
 2218
 2219
 2220
 2221
 2222
 2223
 2224
 2225
 2226
 2227
 2228
 2229
 2230
 2231
 2232
 2233
 2234
 2235
 2236
 2237
 2238
 2239
 2240
 2241
 2242
 2243
 2244
 2245
 2246
 2247
 2248
 2249
 2250
 2251
 2252
 2253
 2254
 2255
 2256
 2257
 2258
 2259
 2260
 2261
 2262
 2263
 2264
 2265
 2266
 2267
 2268
 2269
 2270
 2271
 2272
 2273
 2274
 2275
 2276
 2277
 2278
 2279
 2280
 2281
 2282
 2283
 2284
 2285
 2286
 2287
 2288
 2289
 2290
 2291
 2292
 2293
 2294
 2295
 2296
 2297
 2298
 2299
 2300
 2301
 2302
 2303
 2304
 2305
 2306
 2307
 2308
 2309
 2310
 2311
 2312
 2313
 2314
 2315
 2316
 2317
 2318
 2319
 2320
 2321
 2322
 2323
 2324
 2325
 2326
 2327
 2328
 2329
 2330
 2331
 2332
 2333
 2334
 2335
 2336
 2337
 2338
 2339
 2340
 2341
 2342
 2343
 2344
 2345
 2346
 2347
 2348

5

10